


Chain Tensioner GT

Art. no	Model	Lashing capacity (lb)	L = Min. length	L = Max. length	Weight (lb)
Z101336	GT-8-10	11 240	15.75	23.62	7.28
Z101337	GT-10-10	17 984	15.75	23.62	7.28




Chain, GrabiQ Grade 10 (200)

Short link, KL

Art. no.	Code	WLL lb*	Lashing capacity (lb)	d nom.	P	w1	Weight lb/foot	MPF kN
Z802301	KLA-8-10	5 700	11 240	0.31	0.94	0.43	0.94	63
Z802302	KLA-10-10	8 800	17 984	0.39	1.18	0.55	1.55	98

Fulfills the requirements in ASTM A973/A973M-07(2012) EN 818+2:2008 (WLL +25%, reduced temperature range).

See our Full Range of Chain in Chapter 5



Midgrab MIG with locking pins

Art. no.	Code	WLL lb*	Lashing capacity (lb)	L	X	Y	Weight lb
B14303	MIG CC-8-10	5 700	25 178	3.74	1.97	2.36	1.54
B14313	MIG CC-10-10	8 800	39 565	4.92	2.76	3.03	2.43

Complete set for Lashing GT
with chain, hooks and MIG Shortener



Lashing GT
with GG hooks



Lashing Chain GrabiQ
with hooks in both ends

