


Foundry Hook OKE

Art. no.	Code	WLL lb*	For chain dim.	L	B	E	F	G	H	Weight lb
Z645564	OKE-32-8	72 300	1-1/4"	15.12	5.71	3.54	1.65	3.03	3.70	66.14

Fulfills requirements in: EN 1677:2008, ISO 8539:2009, ASTM A952/A952M and AS 3776:2015.




2

Clevis Shackle GSA

EN 1677-1 Grade 8
 Finish: Painted yellow
 Material: Alloy steel
 Safety factor: 4:1


Art. no.	Code	WLL metric tonnes	For chain dim.	a	c	d2	l	d1	Weight lb
Z700882	GSA-7/8-8	2.0	9/32", 5/16"	1.26	1.42	1.34	2.36	0.63	0.88
Z700883	GSA-10-8	3.2	3/8"	1.34	1.89	1.57	3.15	0.79	1.76
Z700884	GSA-13-8	5.4	1/2"	1.97	2.56	1.73	3.86	0.87	3.09
Z700885	GSA-16-8	8.2	5/8"	2.36	2.76	2.13	4.49	1.06	5.29



Clevis Egglink CEL

Art. no.	Code	WLL lb*	For chain dim.	C	E	G	H	L	Weight lb
Z700968	CEL-7/8-8	4 500	9/32", 5/16"	3.15	1.57	0.55	0.59	3.94	0.88
Z700969	CEL-10-8	7 100	3/8"	3.94	1.97	0.71	0.75	4.96	1.54
Z700970	CEL-13-8	12 000	1/2"	5.12	2.56	0.91	0.98	6.38	3.31


Fulfills requirements in: EN 1677:2008, ISO 8539:2009, ASTM A952/A952M and AS 3776:2015.



Coupling Link GF - Stain Proof**

High strength stainless steel.

Art. no.	Code	WLL lb*	For chain dim.	L	B	F	A	C	Weight lb
B80202	GF-10-8 SP	7 100	3/8"	2.68	0.98	0.43	0.51	1.02	0.66
B80203	GF-13-8 SP	12 000	1/2"	3.50	1.18	0.59	0.63	1.30	1.54
B80204	GF-16-8 SP	18 000	5/8"	4.13	1.42	0.75	0.79	1.57	2.65



* Values converted from metrics and rounded
 **This product comes with a straight pin without recession.