

pewag

**STRONG
IS NOT
ENOUGH**
www.pewag.com

pewag winner inox stainless steel chain system G6 plus

Ideas and solutions in stainless steel



pewag WOX Chain inox

Clean, tidy and hard-working.

This stainless steel lifting chain is made from high-grade stainless steel, with a load capacity that is 25 % higher than that of G5 lifting chains. The chains are tested at 100 % of their load capacity, which is an impressive 12,000 kg! The chain is electrically welded for an extra-clean finish, stamped and with a higher resistance to acids and caustics than the standard lifting chains G8, G10 and G12. The chain is guaranteed to be compatible with the Connex CWI links, with dimensions that are similar to DIN 5687-1 and EN 818-2. The stamp makes the chains clearly identifiable.

The WOX chain is particularly suited for use in water and wastewater applications. It can also be used in connection with chemicals and food products; however, restrictions will apply.



	Code	Nominal diameter dn [mm]	Standard-delivery length [m]	Pitch t [mm]	Inside width b1 min. [mm]	Outside width b2 max. [mm]	WLL [kg]	Breaking force [kN]	Weight [kg/m]
	WOX 4-6	4	50 m	12	6.2	14.8	400	16.0	0.38
	WOX 5-6	5	50 m	15	7.5	18.5	630	25.0	0.58
	WOX 6-6	6	50 m	18	8.7	20.9	900	37.5	0.82
	WOX 7-6	7	50 m	21	9.5	25.2	1,250	50.0	1.11
	WOX 8-6	8	50 m	24	10.8	28.6	1,600	63.0	1.43
	WOX 10-6	10	50 m	30	13.5	36.0	2,500	100.0	2.25
	WOX 13-6	13	25 m	39	17.5	46.8	4,250	170.0	3.77
	WOX 16-6	16	25 m	48	21.5	57.6	6,300	250.0	5.62
	WOX 20-5	20	-	60	27	72	8,000	314.0	9.29
	WOX 26-4+	26	-	78	35.0	93.6	12,000	471.0	16.20

WOX-S Chain inox	Code / Type	Nominal diameter dn [mm]	Pitch t [mm]	inside width b1 min. [mm]	outside width b2 max. [mm]	Breaking force [kN]	weight [kg/m]
	WOX-S 5-6	5	15	6	16.90	25.10	0.57